

IN THE CLAIMS

Please amend the claims as indicated below.

What is claimed is:

- 1 1. (currently amended) A method for determining estimating a parameter of interest
2 of an earth formation with a logging tool having a nuclear radiation source for
3 irradiating said earth formation and a nuclear radiation detector spaced apart from
4 the nuclear radiation source for making measurements resulting from interaction
5 of said irradiation with said earth formation, the method comprising:
6 (a) activating the nuclear radiation source;
7 (a) (b) defining a starting time for a processing time window at which said
8 measurements made by the nuclear radiation detector are responsive
9 primarily to said the parameter of interest;
10 (b) (c) defining an ending time for said the processing time window at which said
11 the measurements are substantially uncontaminated by noise; and
12 (c)(d) analyzing said the measurements within said the processing time window
13 for determining estimating the parameter of interest.
14
- 1 2. (currently amended) The method of claim 1 wherein defining said the start starting
2 time further comprises determining a time at which a value of said the
3 measurements has a predetermined relationship to a determined an estimated

4 value of a parameter of interest at an ending time of a processing time window for
5 an earlier operation of said source.

6

1 3. (currently amended) The method of claim 2 1 wherein said the nuclear radiation
2 source comprises a pulsed neutron source.

3

1 4. (currently amended) The method of claim 2 1 wherein said the measurements
2 made by the nuclear radiation detector comprise gamma ray measurements.

3

1 5. (currently amended) The method of claim 3 wherein said the parameter of interest
2 further comprises at least one of (i) a thermal neutron capture cross section of said
3 the earth formation, (ii) porosity, (iii) formation water salinity, and, (iv) the
4 quantity and type of hydrocarbons contained in pore spaces.

5

1 6. canceled

2

1 7. (currently amended) The method of claim 2 wherein said relationship is of the
2 form

3

$$istr = K / \Sigma$$

4 where *istr* is the start time of a window, *K* is a constant, and Σ is a capture cross
5 section at said the ending time of said the processing time window for said the
6 earlier pulsing operation of said the source.

7

1 8. (currently amended) The method of claim 1 wherein defining said time window
2 ending time the ending time of the processing window further comprises forming
3 a running sum of count rates starting at said the starting time.

4

1 9. (currently amended) The method of claim 8 wherein defining said time window
2 ending time the ending time of the processing window further comprises
3 determining a time at which a count rate has a predetermined relation to said
4 running sum.

5

1 10. (currently amended) The method of claim 1 further comprising partitioning said
2 the processing time window into a plurality of channels (time intervals) having a
3 length depending upon said the start starting time.

4

1 11. (currently amended) An apparatus for use within a borehole penetrating an earth
2 formation for determining estimating a parameter of interest of said earth
3 formation, comprising:

4 (a) a nuclear radiation source for irradiating said the earth formation;
5 (b) a nuclear radiation detector spaced apart from said nuclear radiation source
6 for making measurements resulting from interaction of said irradiation
7 with said earth formation;
8 (c) a processor for which

9 (i) defining defines a starting time for a processing time window for
10 at which said measurements made by the nuclear radiation detector
11 are responsive primarily to said the parameter of interest; and
12 (ii) defining defines an ending time for said the processing time
13 window for at which said the measurements made by the nuclear
14 radiation detector are substantially uncontaminated by noise.

15

1 12. (currently amended) The apparatus of claim 11, wherein said the processor defines
2 said the starting time by determining a time at which a value of said the
3 measurements has a predetermined relation to a determined value of a parameter
4 of interest at an ending time of a processing time window for an earlier operation
5 of said the nuclear radiation source.

6

1 13. (currently amended) The apparatus of claim 12 wherein said the processor further
2 analyzes the measurements within said processing time window and
3 determines said the parameter of interest.

4

1 14. (currently amended) The apparatus of claim 12, wherein said the nuclear radiation
2 source further comprises a pulsed neutron source.

3

1 15. (currently amended) The apparatus of claim 14, wherein said the measurements
2 made by the nuclear radiation detector further comprise gamma ray

3 measurements.

4

1 16. (currently amended) The apparatus of claim 14, wherein said the parameter of
2 interest further comprises at least one of (i) a thermal neutron capture cross
3 section of said the earth formation, (ii) porosity, (iii)formation water salinity, and,
4 (iv) the quantity and type of hydrocarbons contained in pore spaces. [0005]

5

1 17. (currently amended) The apparatus of claim 12, wherein said predetermined
2 relation is of the form

3 $istr = K / \Sigma$

4 where $istr$ is the start time of a window, K is a constant, and Σ is a capture cross
5 section at said the ending time of said the processing time window for said the
6 earlier pulsing operation of said the nuclear radiation source.

7

1 18. (currently amended) The apparatus of claim 11 wherein said the processor defines
2 said the ending time based on forming a running sum of count rates starting at
3 said the starting time.

4

1 19. (original) The apparatus of claim 18, wherein processor defines said ending based
2 on forming a running sum of count rates starting at said starting time.

3

1 20. (original) The method of claim 19, wherein said processor defines said ending

2 time based on determining a time at which a count rate has a predetermined
3 relation to said running sum.

4

1 21. (currently amended) A system for estimating determining a parameter of interest
2 from an earth formation, comprising:

3 (a) a logging tool including:

4 (i) a nuclear radiation source for irradiating said earth formation,
5 (ii) at least one nuclear radiation detector spaced apart from said
6 nuclear radiation source for making measurements resulting from
7 interaction of said irradiation with said earth formation;

8 (b) a processing unit processor for defining a starting time and an ending time
9 for of a time window of for analysis of said measurements made by the
10 nuclear radiation detector, wherein said measurements are responsive
11 primarily to said parameter of interest at said starting time and are
12 substantially uncontaminated by noise at said ending time.

13

1 22. (original) The system of claim 21, wherein said processor defines said start time
2 based on a time at which a value of said measurements have a predetermined
3 relation to a determined value of a parameter of interest at an ending time of a
4 processing time window for an earlier operation of said source.

5

1 23. (currently amended) The system of claim 22 21, wherein said the nuclear radiation

2 source further comprises a pulsed neutron source.

3

1 24. (currently amended) The system of claim 22 21, wherein said measurements made
2 by the nuclear radiation detector further comprise gamma ray measurements.

3

1 25. (currently amended) The system of claim 22, wherein said the parameter of
2 interest further comprises at least one of (i) a thermal neutron capture cross
3 section of said the earth formation, (ii) porosity, (iii)formation water salinity, and,
4 (iv) the quantity and type of hydrocarbons contained in pore spaces.

5

1 26. (currently amended) The system of claim 22, wherein said predetermined relation
2 is of the form

3 $istr = K / \Sigma$

4 where $istr$ is the start time of a window, K is a constant, and Σ is a capture cross
5 section at said the ending time of said the processing time window for said earlier
6 pulsing operation of said source.

7

1 27. (original) The system of claim 21, wherein said processor determines said ending
2 time based on forming a running sum of count rates starting at said starting time.

3

1 28. (original) The system of claim 27, wherein said processor determines said ending
2 time based on determining a time at which a count rate has a predetermined

3 relation to said running sum.

4

1 29. (new) The system of claim 21 further comprising a conveyance device which
2 conveys the tool into a borehole in the earth formation.

3

1 30. (new) The system of claim 21 wherein the conveyance device is one of (i) a
2 wireline, (ii) coiled tubing.

3

1 31. (new) The system of claim 21 further comprising a channel number generator
2 which produces a numerical sequence of memory address codes corresponding to
3 a sequence of adjacent time windows.

4

1 32. (new) The system of claim 21 further comprising a mass storage unit associated
2 with the processor.

3

1 33. (new) The system of claim 31 further comprising a spectrum accumulator.

2

1 34. (new) The system of claim 30 wherein the conveyance device comprises a
2 wireline, the system further comprising a depth controller which provides signals
3 indicative of a depth of said tool.

4